



# CALICO MINERALS PROCESSING, LLC

## SAFETY DATA SHEET

### SECTION 1: CHEMICAL AND MANUFACTURER IDENTIFICATION

**PRODUCT NAME: ALL-AMERICAN 80**

**PRODUCT CODE: 9999D355**

**A.P. Nonweiler Co., Inc.**

3321 County Road A

PO Box 1007

Oshkosh, WI 54903-1007

(920) 231-0850

E-mail: sds@apnonweiler.com

**24 Hour Emergency: INFOTRAC: 1-800-535-5053**

**Outside U.S. and Canada: Infotrac: 352-323-3500**

INFOTRAC Customer ID: 72826

NOTE: INFOTRAC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

**PRODUCT USE: ALCOHOL-BASED HAND SANITIZER**

**Not recommended for:**

Because many of the conditions are within the user's knowledge and control, it is essential that the user evaluate and determine whether the product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

### SECTION 2: HAZARD(S) IDENTIFICATION

Prepared according to Global Harmonized System (GHS) Standards

**GHS Classification Scale**

1=Severe Hazard; 4=Slight Hazard

**GHS Ratings:**

Flammable liquid

2

Flash point < 23°C and initial boiling point > 35°C (95°F)

Eye corrosive

2A

Eye irritant: Subcategory 2A, Reversible in 21 days

Organ toxin single exposure

3

Transient target organ effects | Narcotic effects

Respiratory tract irritation

**GHS Hazards**

H225

Highly flammable liquid and vapour

H319

Causes serious eye irritation

H335

May cause respiratory irritation

H336

May cause drowsiness or dizziness



# CALICO MINERALS PROCESSING, LLC

## SAFETY DATA SHEET

### GHS Precautions

- P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking!
- P233 Keep container tightly closed
- P240 Ground / bond container and receiving equipment
- P241 Use explosion-proof electrical, ventilating, lighting equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray
- P264 Wash thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear protective gloves, protective clothing, eye protection, face protection
- P312 Call a POISON CENTER or doctor/physician if you feel unwell
- P303+P361+P353  
IF ON SKIN (or hair): Remove / Take off all contaminated clothing immediately.  
Rinse skin thoroughly with water / shower
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305+P351+P338  
IF IN EYES: Rinse continuously with cool water for at least 15 minutes.  
Remove contact lenses if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists get medical advice / attention
- P370+P378 In case of fire: Use dry chemical / CO2 / foam for extinction
- P405 Store locked up
- P403+P233 Store in a well ventilated area. Keep container tightly closed.
- P403+P235 Store in a well ventilated area. Keep cool
- P501 Dispose of contents / container to an approved waste disposal facility

Signal word: **Danger**





# CALICO MINERALS PROCESSING, LLC

## SAFETY DATA SHEET

### SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NUMBER	WEIGHT CONCENTRATION %
Ethyl alcohol	64-17-5	70.00% - 80.00%
Isopropyl alcohol	67-63-0	1.00% - 5.00%
Aloe Barbadensis Leaf Juice	94349-62-9	1.00% - 5.00%
Cellulose hydroxypropyl methyl ether	9004-65-3	0.10% - 1.00%
Hydrogen peroxide	722-84-1	0.10% - 1.00%

### SECTION 4: FIRST AID MEASURES

**Inhalation:** Move affected person to fresh air. If breathing has stopped, administer CPR. If the person vomits, clean the airway and turn their head to the side to prevent choking. If the person is unconscious but breathing, place them stably on their left side in the recovery position. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

**Eyes:** Flush eyes gently with clean water for at least 15 minutes. If irritation persists, seek immediate medical attention.

**Skin:** If on skin: No emergency care anticipated. No evidence of adverse effects based on available information. May cause mild irritation. Contact may cause: cracking, drying, redness.

**Ingestion:** Rinse mouth with water to remove any residual chemical. If the person vomits, clean their airway and turn their head to the side to prevent choking. DO NOT induce vomiting and DO NOT give them anything to drink unless directed to do so by a physician. If the person is unconscious but breathing, place them stably on their left side in recovery position. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

**Additional Notes to Physician - Treat symptomatically. No specific antidote available**



# CALICO MINERALS PROCESSING, LLC

## SAFETY DATA SHEET

### SECTION 5: FIREFIGHTING MEASURES

Flash Point: 12 C (54 F) | LEL: 3.0% | UEL: N/A

#### **Suitable Extinguishing Media:**

Foam | Carbon Dioxide (CO<sub>2</sub>) | Dry Chemical

**Specific Hazards During Firefighting:** Prevent firefighting run-off from entering drains or sewers. Byproducts of Combustion: Fires involving this product may release oxides of carbon and nitrogen, reactive hydrocarbons, and irritating vapors.

**Unusual Fire and Explosion Hazards:** Any closed container may rupture when exposed to extreme heat. Use a water spray to cool sealed containers. Solvent vapors are heavier than air and can travel along the ground.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### **Spill / Leak Clean-Up Procedures:**

Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spills, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers. If a large spill occurs notify the appropriate authorities.

***In case of road spill or accident contact INFOTRAC (1-800-535-5053).***

**CAUTION:** If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will also be regulated.

**Do not empty into drains.** All disposal must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.



# CALICO MINERALS PROCESSING, LLC

## SAFETY DATA SHEET

### SECTION 7: HANDLING AND STORAGE

**Handling Precautions:** Open containers carefully and in a well ventilated area, and use appropriate respiratory protection. Wash hands thoroughly after handling. Keep containers closed when not in use. Do not transfer to unmarked containers. Empty containers contain product residue which may exhibit hazardous properties therefore, do not pressurize, cut, glaze, weld or use for any other purpose. Return drums to reclamation center for proper cleaning and reuse.

**Storage Requirements:** Store in a cool, dry, well ventilated area. Keep containers tightly closed and store away from heat, sparks, open flame or oxidizing materials. Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition.

### SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

CHEMICAL NAME / CAS NO.	OSHA EXPOSURE LIMITS	ACGIH EXPOSURE LIMITS	OTHER EXPOSURE LIMITS
Ethyl alcohol 64-17-5	1000 ppm TWA; 1900 mg/m <sup>3</sup> TWA	1000 ppm STEL	NIOSH: 1000 ppm TWA; 1900 mg/m <sup>3</sup> TWA
Isopropyl alcohol 67-63-0	400 ppm TWA; 980 mg/m <sup>3</sup> TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m <sup>3</sup> TWA 500 ppm STEL; 1225 mg/m <sup>3</sup> STEL
Aloe Barbadensis Leaf Juice 94349-62-9	Not Established	Not Established	Not Established
Cellulose hydroxypropyl methyl ether 9004-65-3	Not Established	Not Established	Not Established
Hydrogen peroxide 7722-84-1	1 ppm TWA; 1.4 mg/m <sup>3</sup> TWA	1 ppm TWA	NIOSH: 1 ppm TWA; 1.4 mg/m <sup>3</sup> TWA

**Engineering Controls:** Avoid creating dust or mist. Local exhaust ventilation, process enclosures, or other engineering controls are required when handling or using this product to avoid over exposure. Use explosion-proof ventilation equipment. Do not use in closed or confined spaces. Keep all levels below exposure limits. Perform regular monitoring to ensure exposure limits are not exceeded.



# CALICO MINERALS PROCESSING, LLC

## SAFETY DATA SHEET

### Personal Protective Equipment (PPE):

**Respiratory Protection** - Do not breathe vapors. When concentrations exceed the established limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA) until vapors are exhausted. Observe OSHA standard 29 CFR 1910.134 and ANSI Z88.2 requirements whenever workplace conditions require a respirators use.

**Hand Protection/Skin Protection** - Material is not considered a skin contact hazard.

**Eye Protection** - Not required for normal use. If splashing of liquid may occur, then wear a face shield. Use additional eye protection such as chemical safety goggles when the possibility for eye contact from splashing, spraying liquid, or airborne material exists. When handling large quantities, eye wash stations and deluge showers should be available.

### Hygiene Measures:

**General** - When using do not eat or drink. Wash hands with soap and water before breaks and at the end of each workday.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

This mixture typically exhibits the following properties under normal circumstances:

<p><b>Appearance</b> Liquid Dispersion</p> <p><b>Physical State</b> Liquid</p> <p><b>Lbs VOC/Gallon Less Water</b> 6.46</p> <p><b>g VOC/L Less Water</b> 774.60</p>	<p><b>Odor</b> Alcohol</p> <p><b>Specific Gravity (SG)</b> 0.837</p> <p><b>Flash point:</b> 12°C, 54°F</p> <p><b>Boiling range:</b> 78 - 100°C</p>
---	--

## SECTION 10: STABILITY AND REACTIVITY

**Product Stability (under normal conditions):** STABLE

**Incompatible Materials:** Strong acids, strong bases, oxidizing agents

**Hazardous Decomposition Products:** Carbon Dioxide (CO<sub>2</sub>), Carbon Monoxide (CO), Oxides of Nitrogen (NO<sub>x</sub>), dense black smoke

*Hazardous polymerization will not occur.*



# CALICO MINERALS PROCESSING, LLC

## SAFETY DATA SHEET

### SECTION 11: TOXICOLOGICAL INFORMATION

**Mixture Toxicity:** Inhalation Toxicity LC50: 195mg/L

**Note -** Toxicological studies have not been performed on this mixture. The toxicological data listed is compiled using data from the components of the mixture. Refer to Section 2 of this SDS for GHS classification of acute and chronic effects of exposure.

**Principle Routes of Exposure:** Inhalation Skin Contact Eye Contact Ingestion.

**May cause damage to the following organs:** Blood, Eyes, Liver, Central Nervous System, Reproductive System Skin, Respiratory System

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing) or ACGIH (optional listing):

CAS Number	Description	% Weight	Carcinogen Rating
64-17-5	Ethyl alcohol	70% - 80%	IARC: Human carcinogen OSHA: listed

### SECTION 12: ECOLOGICAL INFORMATION

**Bioaccumulative Potential:** No data available | **Mobility in Soil:** No data available

**Persistence and Degradability:** No data available

#### Component Ecotoxicity:

##### Ethyl alcohol

96 Hr LC50 Oncorhynchus mykiss: 12.0 - 16.0 mL/L [static]; 96 Hr LC50 Pimephales promelas: >100 mg/L [static]; 96 Hr LC50 Pimephales promelas: 13400 - 15100 mg/L [flow-through]  
48 Hr LC50 Daphnia magna: 9268 - 14221 mg/L; 48 Hr EC50 Daphnia magna: 2 mg/L [Static]

##### Isopropyl alcohol

96 Hr LC50 Pimephales promelas: 9640 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 11130 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >1400000 µg/L  
48 Hr EC50 Daphnia magna: 13299 mg/L  
96 Hr EC50 Desmodesmus subspicatus: >1000 mg/L; 72 Hr EC50 Desmodesmus subspicatus: >1000 mg/L

##### Hydrogen peroxide

96 Hr LC50 Pimephales promelas: 16.4 mg/L; 96 Hr LC50 Lepomis macrochirus: 18 - 56 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 10.0 - 32.0 mg/L [static]  
48 Hr EC50 Daphnia magna: 18 - 32 mg/L [Static]



# CALICO MINERALS PROCESSING, LLC

## SAFETY DATA SHEET

### SECTION 13: DISPOSAL CONSIDERATIONS

Do not discharge product into sewer system. Dispose of in a licensed facility. Waste management should be in full compliance with federal, state, and local laws.

The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing, or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

### SECTION 14: TRANSPORT INFORMATION

This material is classified for transport as follows:

Agency	Proper Shipping Name	UN Number	Packing Group	Hazard Class
U.S. DOT	ALCOHOL, N.O.S. (CONTAINS ETHYL ALCOHOL, ISOPROPYL ALCOHOL)	1987	II	3

### SECTION 15: REGULATORY INFORMATION

Additional regulatory listings where applicable

#### State of California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING! This product contains the following substance(s) which are listed by the State of California as carcinogenic, or a reproductive toxin: 64-17-5 Ethyl alcohol Carcinogen

**Clean Air Act, Section 112, Hazardous Air Pollutants (HAPs) (see 40 CFR 61)** This product contains the following substance(s) which are listed as hazardous air pollutants (HAPs) per the Clean Air Act: None

**Massachusetts Right To Know** This product contains the following toxic or hazardous substance(s) which appear on the Massachusetts Substance List:

64-17-5 Ethyl alcohol  
67-63-0 Isopropyl alcohol

#### New Jersey Worker and Community Right to Know Hazardous Substance List

The following substance(s) appear on the New Jersey Right to Know Hazardous Substance List:  
64-17-5 Ethyl alcohol





# CALICO MINERALS PROCESSING, LLC

## SAFETY DATA SHEET

**Commonwealth of Pennsylvania Worker and Community Right To Know Act** This product contains the following substance(s) which appear on the Pennsylvania Hazardous Substance List:  
64-17-5 Ethyl alcohol  
67-63-0 Isopropyl alcohol

**Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA)**  
This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40, of the Code of Federal Regulations, part 372: 67-63-0 Isopropyl alcohol

Country	Regulation	All Components Listed
Australia	Australian Inventory of Chemical Substances	No
Japan	Existing and New Chemical Substances	No
China	Inventory of Existing Chemical Substances Produced	No
New Zealand	Inventory of Chemicals	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Reach PBT/vPvB	No

**TSCA Substance Control Act (TSCA)** All substances except those listed below appear in the Toxic Substances Control Act, Chemical Substance Inventory: None

### SECTION 16: OTHER INFORMATION

**Disclaimer:** The Volatile Organic Compound (VOC) content reported herein, if any, is based on a material VOC calculation. Several methods are used for the calculation of VOC content, and the standards and requirements regarding VOC content vary by location or jurisdiction.

This document has been prepared using data from sources considered to be technically reliable and is believed to be correct as of the date hereof. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use, and to comply with all federal, state, provincial, and local laws and regulations.